

Visual Sensations™

CRT

21" (19.9" VIS) High Performance,
High Contrast Picture Tube,
Anti-Reflection & Anti-Static Coating

MAXIMUM RESOLUTION

1920 x 1440 @ 75Hz

DOT PITCH

0.22mm Horizontal Dot Pitch
(0.25mm Dot Pitch)

FREQUENCY

Horizontal: 30 ~ 117KHz
Vertical: 50 ~ 160Hz

BANDWIDTH

230MHz

SIGNAL CONNECTOR

15-pin D-Sub. (Analog R,G,B)

FEATURES

Superb Image Quality
On-Screen Digital Controls
Plug & Play (VESA DDC 2B)
PC & Mac* Compatible
Tilt & Swivel Base

REGULATORY APPROVALS

UL, G/S, FCC Class B, DHHS, MPR II
SEMKO, NUTEK, CE, EPA, TCO 95,
ISO 9001, ISO 14001

POWER SUPPLY

100-240 VAC, 50/60 Hz,
Auto Switching

MONITOR DIMENSIONS

19.9"(W) x 20.9"(D) x 19.1"(H)
506mm(W) x 527mm(D) x 485mm(H)

BOX DIMENSIONS

24.6"(W) x 22.5"(D) x 22.6"(H)
625mm(W) x 572mm(D) x 574mm(H)

WEIGHT

Net: 63.4 lbs. / 28.8 Kg.
Gross: 73.7 lbs. / 33.5 Kg.

WARRANTY

3 Year Limited Parts & Labor
KDS Advanced Replacement Express Service

21" High Performance Monitor

VS-21e

21" High Performance Monitor



The **VS-21e** is designed for imaging and CAD/CAM/CAE professionals who want maximum performance from today's technology. A powerful tool for high-end graphics, production, scientific and engineering design applications, its advanced features deliver sharp pictures, crisp colors and precise lines with virtually no eyestrain.



www.kdsusa.com **KDS**

©2002 KDS USA Inc. All rights reserved. Specifications, design, availability and warranty subject to change without notice. This document is used for reference only. KDS USA is not responsible for any errors. *Mac adapters may be required.